



AP - 520SC
Combination Locking



AP - 520SET
Digital Locking

SPECIFICATIONS

MODEL	EXTERNAL DIMENSIONS* H x W x D (mm)	DOOR STEEL PLATE	BODY STEEL PLATE	WEIGHT
AP - 520SC LG 3 wheel combination lock	455 x 345 x 300	10mm	6mm	50Kg
AP - 520SET Digital lock with time delay	455 x 345 x 300	10mm	6mm	50Kg

* Weights and dimensions are approximate. The safe pictures shown on this brochure are for illustrative purpose only.

- ◆ Built from heavy steel plate.
- ◆ Heavy duty 10mm steel plate door and 6mm steel safe body reinforced with steel bar all around front edges.
- ◆ Two 25mm locking bolts.
- ◆ AP - 520SC is fitted with quality UL rated 3 wheel combination lock mounted on hardened steel plate and has secondary re-locking device.
- ◆ Mounting: 4 x 12mm mounting holes in base.

MAIN FEATURES FOR AP - 520SET:

- ◆ Quality UL rated swing bolt safe lock mounted on hardened steel plate.
- ◆ Secondary relocking system.
- ◆ 30 user codes (including two management codes) plus emergency codes. Two security levels.
- ◆ Programmable time delay up to 99 minutes.
- ◆ Errant access lockout feature.
- ◆ External battery – hook on key pad. One 9 volt Alkaline battery (very low battery consumption).
- ◆ Metal key pad housing.
- ◆ Bright LCD screen display – guide you through all the programming procedures, and shows current battery voltage.
- ◆ Dual Mode (two codes required to open safe).

SECUGUARD® safes are covered by a two year warranty excluding freight & travelling, with a 12 month warranty on locks.