



AP - 7038SEK
Digital Locking

MODEL	EXTERNAL DIMENSIONS* H x W x D (mm)	DOOR STEEL PLATE	BODY STEEL PLATE	WEIGHT
AP - 7038SEK UL certified digital lock with time delay	700 x 380 x 360	10mm	6mm	94Kg

The safe pictures shown on this brochure are for illustrative purpose only. Weights and dimensions are approximate. We reserve the right to alter specifications without notice or obligation.

SECUGUARD® safes are covered by a twelve month warranty excluding freight & travelling.

- ◆ Built from heavy steel plate.
- ◆ Heavy duty 10mm solid steel plate door and 6mm solid steel safe body reinforced with steel frame all around front edges.
- ◆ 25mm solid steel bolt work.
- ◆ Quality UL certified swing bolt electronic safe lock mounted on 6mm casehardened steel plate.
- ◆ Secondary re-locking device in case of tampering.
- ◆ Internal lockable compartment fitted with pick resistant lever lock.
- ◆ Programmable 30 user codes (including two management codes) plus emergency codes. Two security levels.
- ◆ Programmable time delay up to 99 minutes.
- ◆ Dual Mode.
- ◆ Errant access lockout feature.
- ◆ External battery – hook on key pad. One 9 volt Alkaline battery (very low battery consumption).
- ◆ Metal key pad housing.
- ◆ Bright LCD screen display – guide you through all the programming procedures, and shows current battery voltage.
- ◆ Mounting: 4 x 12mm mounting holes in base.
- ◆ Powder coated hammer tone silver finish.