



# DEPOSIT SAFES



**AP - 520SDK**  
Dual Key Locking



**AP - 520SC**  
Combination Locking



**AP - 520SET**  
Digital Locking

MODEL	EXTERNAL DIMENSIONS* H x W x D (mm)	DOOR STEEL PLATE	BODY STEEL PLATE	WEIGHT
<b>AP - 520SDK</b> Dual ROSS locks	455 x 345 x 300	10mm	6mm	50Kg
<b>AP - 520SC</b> UL listed 3 wheel combination lock	455 x 345 x 300	10mm	6mm	50Kg
<b>AP - 520SET</b> UL listed digital lock with time delay	455 x 345 x 300	10mm	6mm	50Kg

The safe pictures shown on this brochure are for illustrative purpose only. Weights and dimensions are approximate. We reserve the right to alter specifications without notice or obligation.

**SECUGUARD® safes are covered by a twelve month warranty excluding freight & travelling.**

- ❖ Built from heavy steel plate.
- ❖ Heavy duty 10mm steel plate door and 6mm steel safe body reinforced with steel frame all around front edges.
- ❖ 25mm solid locking bolts.
- ❖ AP - 520SC is fitted with quality UL listed 3 wheel combination lock mounted on 6mm case hardened steel plate. Secondary re-locking device.
- ❖ AP - 520SDK is fitted with quality Australian made pick resistant lever locks mounted on 6 mm case hardened steel plate.
- ❖ Mounting: 4 x 12mm mounting holes in base.
- ❖ Powder coated hammer tone silver finish.

#### MAIN FEATURES FOR AP - 520SET:

- ❖ Quality UL listed swing bolt electronic safe lock mounted on 6mm casehardened steel plate.
- ❖ Secondary re-locking system.
- ❖ Programmable 30 user codes (including two management codes) plus emergency codes. Two security levels.
- ❖ Programmable time delay up to 99 minutes.
- ❖ Errant access lockout feature.
- ❖ External battery – hook on key pad. One 9 volt Alkaline battery (very low battery consumption).
- ❖ Metal key pad housing.
- ❖ Bright LCD screen display – guide you through all the programming procedures, and shows current battery voltage.
- ❖ Dual Mode.